

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 12362-3 (1994): Agricultural vehicles - Mechanical connections on towing vehicles, Part 3: Tractor drawbar [FAD 11: Agricultural Tractors and Power Tillers]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक

कृषि वाहन — कर्षण वाहनों में यान्त्रिक संयोजन

भाग 3 ट्रैक्टर ड्राबार

(पहला पुनरीक्षण)

Indian Standard

AGRICULTURAL VEHICLES — MECHANICAL
CONNECTIONS ON TOWING VEHICLES

PART 3 TRACTOR DRAWBAR

(First Revision)

UDC 631.373 : 629.114.3.013.83

© BIS 1994

BUREAU OF INDIAN STANDARDS

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

April 1994

Price Group 2

NATIONAL FOREWORD

This Indian Standard, which is identical with ISO 6489-3 : 1992 'Agricultural vehicles — Mechanical connections on towing vehicles — Part 3 : Tractor drawbar', issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of the Agricultural Tractors and Power Tillers Sectional Committee (FAD 32) and approval of the Food and Agriculture Division Council.

IS 12362 : 1988, Technical requirement for towing connection of agricultural tractors was prepared based on ISO 6489/1 : 1980 Agricultural Vehicles — Mechanical connection on towing vehicles — Part 1 : Hook type and ISO 6489/2 : 1980, Agricultural vehicles — Mechanical connection on towing vehicles — Part 2 : Clevis type. Now ISO 6489 has been revised into following three parts:

ISO 6489 (Part 1) Agricultural vehicles — Mechanical connection on towing vehicles — Part 1 : Hook type

ISO 6489 (Part 2) Agricultural vehicles — Mechanical connection on towing vehicles — Part 2 : Clevis type and

ISO 6489 (Part 3) Agricultural vehicles — Mechanical connection on towing vehicles — Tractor draw-bar

In order to make it more implementable and to align with the corresponding above mentioned International Standards IS 12362 : 1988 is revised. In revision of IS 12362 : 1988 the three parts of ISO 6489 have been adopted as dual number standards with splitting IS 12362 into following three parts:

IS 12362 (Part 1) Agricultural vehicles — Mechanical connection on towing vehicles — Part 1 : Hook type

IS 12362 (Part 2) Agricultural vehicles — Mechanical connection on towing vehicles — Part 2 : Clevis type

IS 12362 (Part 3) Agricultural vehicles — Mechanical connection on towing vehicles — Tractor drawbar

In the adopted standard certain terminology and conventions are not identical with those used in the Indian Standards; attention is drawn specially to the following:

- a) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.
- b) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'.

In this Indian Standard, the following International Standards have been referred. The list of corresponding Indian Standards are given below:

<i>International Standard</i>	<i>Indian Standard</i>	<i>Degree of Correspondence</i>
ISO 500 : 1991 Agricultural tractors — Rear-mounted power take-off — Types 1, 2 and 3	IS 4931 : 1993 Technical requirements for power take-off of agricultural tractors	Technically equivalent
ISO 730-1 : 1990 Agricultural wheeled tractors — Rear-mounted three-point linkage — Part 1 : Categories 1, 2 and 3	IS 4468 (Part 1) : 1993 Agricultural wheeled tractors — Rear-mounted three point linkage : Part 1 Categories 1, 2 and 3	Identical

Indian Standard

AGRICULTURAL VEHICLES — MECHANICAL CONNECTIONS ON TOWING VEHICLES

PART 3 TRACTOR DRAWBAR

(First Revision)

1 Scope

This part of ISO 6489 specifies the dimensional requirements, location and vertical static loads for drawbars on agricultural tractors.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 6489. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 6489 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 500:1991, *Agricultural tractors — Rear-mounted power take-off — Types 1, 2 and 3.*

ISO 730-1:1990, *Agricultural wheeled tractors — Rear-mounted three-point linkage — Part 1: Categories 1, 2 and 3.*

3 Dimensions and location

The tractor drawbar dimensions are related to the three categories specified in ISO 730-1.

The hitch end of the tractor drawbar shall normally be designed as a clevis.

When the drawbar is positioned in the longitudinal mid-plane of the tractor, the relationship between the location of the power take-off (PTO) as defined in ISO 500 and the drawbar shall comply with figure 1 and table 1.

For special applications, other drawbar locations may be used (see annex A).

It shall be possible to secure swinging drawbars in the longitudinal mid-plane position.

4 Vertical static loads

The static load according to table 1 is the minimum load the tractor drawbar shall be able to withstand or conversely the maximum static load which equipment may impose upon the tractor drawbar.

The dynamic loads imposed upon the tractor drawbar and equipment hitch will be considerably higher than the static load ratings. These loads are also subject to consideration being given to the capacity of tyres and to other aspects of tractor specifications and the conditions relating to its use.

For special applications, other vertical static loads may be used (see annex A).

NOTE 1 Requirements for tractor drawbars may be subject to legal provisions by governmental authorities.

Dimensions in millimetres




Figure 1 — Location and dimensions of drawbar

Table 1 — Drawbar dimensions, location and vertical load

Dimensions in millimetres

Category according to ISO 730-1	Clevis dimensions		Clevis envelope r ¹⁾	Location		Vertical load (see clause 4) F kN
	d $^{+1}_0$	b min.		c ²⁾ min.	l ± 10	
1	33	60	70	200	400	8
2	33	60	70	220	400	12
3	33	70	80	250	500	15

1) The clevis may have any configuration within the envelope defined by radius r (see figure 1).
2) For special applications, the top portion of the clevis may be removed to maintain dimension c .

Annex A (normative)

Drawbar locations for special applications

For special applications, other drawbar locations and related vertical loads can be used, for example

— a "short" position, intended to connect non-PTO-driven equipment which applies a high vertical load to the drawbar; or

— an "extended" position, intended for a special PTO drive-shaft condition where equal angularity of the drive-shaft joints cannot be obtained using the normal position.

In such cases the drawbar length and the vertical loads given in table A.1 shall be used.

Table A.1 — Drawbar locations for special applications

Dimensions in millimetres

Category according to ISO 730-1	Location (see figure 1) <i>l</i> ±10		Vertical load (see clause 4) <i>F</i> kN	
	Short position ¹⁾	Extended position	Short position	Extended position
1	250	500	15	6,5
2	250	550	22,5	8
3	350	650	27	10
1) 25 mm minimum dimension shown in figure 1 does not apply.				

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc : No. FAD 32 (183)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha
(Common to all Offices)

Regional Offices :

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 31 331 13 75
Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	{ 37 84 99, 37 85 61, 37 86 26, 37 86 62
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 53 38 43, 53 16 40, 53 23 84
Southern : C. I. T. Campus, IV Cross Road, MADRAS 600113	{ 235 02 16, 235 04 42, 235 15 19, 235 23 15
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	{ 632 92 95, 632 78 58, 632 78 91, 632 78 92
Branches : AHMADABAD, BANGALORE, BHOPAL, BHUBANESHWAR, COIMBATORE, FARIDABAD, GHAZIABAD, GUWAHATI, HYDERABAD, JAIPUR, KANPUR, LUCKNOW, PATNA, THIRUVANANTHAPURAM.	

Reprography Unit, BIS, New Delhi, India